



## Two-dimensional electron gases in SrTiO<sub>3</sub>-based complex oxide heterostructures with electron mobilities exceeding 100,000 cm<sup>2</sup>V<sup>-1</sup>s<sup>-1</sup>

Chen, Yunzhong; Pryds, Nini

*Publication date:*  
2013

[Link back to DTU Orbit](#)

### *Citation (APA):*

Chen, Y., & Pryds, N. (2013). *Two-dimensional electron gases in SrTiO<sub>3</sub>-based complex oxide heterostructures with electron mobilities exceeding 100,000 cm<sup>2</sup>V<sup>-1</sup>s<sup>-1</sup>*. Abstract from EMN West meeting, Energy materials Nanotechnology, Houston, TX, United States.

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

## Two-dimensional electron gases in SrTiO<sub>3</sub>-based complex oxide heterostructures with electron mobilities exceeding 100,000 cm<sup>2</sup>V<sup>-1</sup>s<sup>-1</sup>

Yunzhong Chen\*, Nini Pryds

*Department of Energy Conversion and Storage, Technical University of Denmark, Risø Campus, 4000 Roskilde, Denmark*

*Email: yunc@dtu.dk, web site: <http://www.ecs.dtu.dk/English.aspx>*

The high-mobility two-dimensional electron gas (2DEG) confined at the interface of two insulating complex oxides provides new opportunities to explore nanoelectronic devices. So far, such oxide 2DEG is nearly exclusively created within the frame of interface polarity, such as the case of the intensively explored LaAlO<sub>3</sub>/SrTiO<sub>3</sub> (LAO/STO) heterointerface. Alternatively, when building heterostructures on STO, the basis material for oxide electronics, the conductance can also originate from tunable redox reactions at the interface, i. e. the oxygen-vacancies dominated conductivity in reduced STO substrates [1]. In this presentation, the mechanism of the interface conductance in STO-based oxide heterostructures will be discussed. Moreover, our recent findings of new 2DEGs in STO-based oxide heterostructures will be also present. Relying on redox reactions, an oxide 2DEG with electron mobilities exceeding 100,000 cm<sup>2</sup>V<sup>-1</sup>s<sup>-1</sup> at 2 K, 100 times higher than those of LAO/STO heterointerface, is obtained [2]. The conduction dimension and its spatial confinement will be also discussed.

1. Y. Z. Chen *et al.*, *Nano Lett.* **11**, 3774 (2011).
2. Y. Z. Chen *et al.*, *Nature Communications*. (2012) (accepted).

<b>Presentation Method (Invited/Regular Oral/Poster): Invited</b>
---